

CSS-Menü

Beispielcode für ein einfaches Menü

```
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<html>
<head>
<meta content="text/html; charset=utf-8" http-equiv="Content-Type">
<title>Batix Testmenü mit CSS</title>
<link rel="stylesheet" href="batix-css-menue.css" type="text/css">
</head>
<body>

<div class="BX_cssmenue">
  <ul>
    <bx:sitemap.0>
      <li><!--[if IE]><!--><a<bx:sitemap.if hasChilDs> class="submenu"</bx:sitemap.if>
href="/www/<bx:pagedata.webdir/>/<bx:navigation.path/>/" target="<bx:navigation.target
default="_self"/>" title="<bx:navigation.meta name="meta"/>"><!--<![endif]--
><bx:sitemap.name/>
      <!--[if gt IE 6]><!--></a><!--<![endif]--><!--[if lte IE 6]><table><tr><td><!--[endif]-->
      <bx:sitemap.if hasChilDs><ul></bx:sitemap.if>
      <bx:sitemap.1>
        <li class="<bx:sitemap.if first>firstitem</bx:sitemap.if><bx:sitemap.if
last>lastitem</bx:sitemap.if"><a<bx:sitemap.if hasChilDs> class="submenu"</bx:sitemap.if>
href="/www/<bx:pagedata.webdir/>/<bx:navigation.path/>/" target="<bx:navigation.target
default="_self"/>" title="<bx:navigation.meta name="meta"/>"><bx:sitemap.name/>
        <!--[if gt IE 6]><!--></a><!--<![endif]--><!--[if lte IE
6]><table><tr><td><!--[endif]-->
        <bx:sitemap.if hasChilDs><ul></bx:sitemap.if>
        <bx:sitemap.2>
          <li class="<bx:sitemap.if first>firstitem</bx:sitemap.if><bx:sitemap.if
last>lastitem</bx:sitemap.if"><a<bx:sitemap.if hasChilDs> class="submenu"</bx:sitemap.if>
href="/www/<bx:pagedata.webdir/>/<bx:navigation.path/>/" target="<bx:navigation.target
default="_self"/>" title="<bx:navigation.meta name="meta"/>"><bx:sitemap.name/></a></li>
          </bx:sitemap.2>
        </li>
      </ul>
    </bx:sitemap.0>
  </ul>
</div>
```

```

        <bx:sitemap.if hasCHilds></ul></bx:sitemap.if>
        <!--[if lte IE 6]></td></tr></table></a><![endif]-->
    </li>
</bx:sitemap.1>
<bx:sitemap.if hasCHilds></ul></bx:sitemap.if>
<!--[if lte IE 6]></td></tr></table></a><![endif]-->
</li>
</bx:sitemap.0>
</ul>
</div>

</body>
</html>

```

Beispiel für die dazugehörige css-Datei

```

.BX_cssmenue {
width:600px;
height:25px;
border:1px solid #98b1c4;
background:#bdcedc;
z-index:100;
position:relative;
}
.BX_cssmenue ul {
float:left;
list-style-type:none;
position:relative;
margin:0;
padding:0;
}
.BX_cssmenue li {
float:left;
}
.BX_cssmenue li:hover,.BX_cssmenue li a:hover {
position:relative;
}
.BX_cssmenue a {
display:block;
float:left;

```

```
height:25px;
white-space:nowrap;
padding:0 10px 0 10px;
line-height:25px;
font-size:12px;
font-weight:bold;
font-family:Arial,Helvetica,sans-serif;
text-align:center;
color:#293d6b;
text-decoration:none;
}
.BX_cssmenu li:hover a,.BX_cssmenu a:hover {
background:#98b1c4;
}
.BX_cssmenu a.submenu {
background:url(/static/dev/css-menu/top-sub.gif) no-repeat center right;
padding:0 20px 0 10px;
}
.BX_cssmenu li:hover a.submenu,.BX_cssmenu a.submenu:hover {
background:#98b1c4 url(/static/dev/css-menu/top-sub.gif) no-repeat center right;
}
.BX_cssmenu ul ul {
position:absolute;left:-5000px;
top:-5000px;
width:202px;
height:auto;
border:none;
background:#bdcedc;
}
.BX_cssmenu table {
margin-top:-1px;
border-collapse:collapse;
}
.BX_cssmenu ul :hover ul {
left:0px;
top:25px;
}
.BX_cssmenu li li {
width:200px;
border:1px solid #98b1c4;
```

```
border-width:0 1px;
padding:0
}
.BX_cssmenu li li.firstitem {
border-top:1px solid #98b1c4;
}
.BX_cssmenu li li.lastitem {
border-bottom:1px solid #98b1c4;
}
.BX_cssmenu ul ul a,.BX_cssmenu ul :hover ul a,.BX_cssmenu ul :hover ul :hover ul a {
float:none;
margin:0;
width:180px;
height:auto;
white-space:normal;
padding:4px 10px 5px 10px;
font:bold 12px Arial,Helvetica,sans-serif;
text-decoration:none;
text-align:left;
color:#293d6b;
background:none;
}
.BX_cssmenu ul ul :hover a,.BX_cssmenu ul ul a:hover,.BX_cssmenu ul ul :hover ul :hover
a,.BX_cssmenu ul ul :hover ul a:hover {
background:#98b1c4;
}
.BX_cssmenu ul ul a.submenu,.BX_cssmenu ul :hover ul a.submenu {
width:180px;
padding:4px 10px 5px 10px;
background:url(/static/dev/css-menu/sub-sub.gif) no-repeat center right;
}
.BX_cssmenu ul ul :hover a.submenu,.BX_cssmenu ul ul a.submenu:hover {
background:#98b1c4 url(/static/dev/css-menu/sub-sub.gif) no-repeat center right;
}
.BX_cssmenu ul :hover ul ul {
position:absolute;
left:-5000px;
top:-5000px;
}
.BX_cssmenu ul :hover ul :hover ul {
```

```
left:190px;
top:-1px;
}
.BX_cssmenu br {
clear:both;
height:0;
font-size: 1px;
line-height: 0px;
}
```

Link zur Demo-Seite mit diesem Code <http://dev.batix.local/www/dev/purecssmenu/>